



NLHRADD

Electric radiator

Technical features

Digital temperature selector for displaying real temperature, set up temperature, clock and other messages.

Weekly/daily programmer.

Built-in ambient thermostat $\pm 0,1^{\circ}\text{C}$.

Electronic Triac control optimizer ETCO, to manage and restrict the flow of electricity.

Adjustable digital thermostat.

Three-level temperature selector: Comfort, Economy and Frost-protection.

Flat lockable keyboard for easy cleaning.

Built-in On-Off switch.

Ratings from 500 to 2000 W.

Thermal safety cut out.

Class I insulation.

Stylish aluminium body finished in epoxy powder coating RAL 9010.

Fitted with mains cable.

Patented safety wall fixing brackets for ease of installation.

MODEL	NLHRADD500	NLHRADD750	NLHRADD1000	NLHRADD1250	NLHRADD1500	NLHRADD2000
Type	Digital Control with Programmable 24/7 timer					
Modules	4	6	8	10	12	14
W (cm)	41.5	57.5	73.5	89.5	105.5	121.5
D (cm)	10 (plus 2 cm separated from the wall)					
H (cm)	58	58	58	58	58	58
Weight (kg)	9.5	13	16.5	20	23.5	27
Input (W)	500	750	1000	1250	1500	2000
Voltage	220 -240 V~					