

Description

Starlet Recessed LED Round Panel Light c/w remote Plug & Play Driver



General

Colour Options	White Bezel Only
Light Source	Non Replaceable LED Module
LED Expected Life	30,000 Hours Average Life
Product Warranty	3 Years from Date of Purchase
Mounting Method	Ceiling Recessed

Electrical Parameters

Supply Voltage	220-240v AC
Frequency	50/60 Hz
Circuit Wattage	12W Including Driver
Circuit Current	0.06 Amps
Driver mA Rating	300mA
PFC	0.75
In Rush Current	0.1Amps Max Peak

Classifications and Approvals

Earth Class	Class II, No Earth Required
IP Rating	IP20
Fire Rating (Part B)	No
Sound Insulating (Part E)	No
Air & Moisture Rated (Part C)	No
Efficiency Rated (Part L)	Yes Part L Compliant
Energy Rating	A+
CE Marked	Yes
Designed In Accordance to	BSEN60598, EN55015, EN61347

Installation

Cut-out	155mm
Minimum Void	60mm
Insulation	Must Remain in Free Air Space
Working Ambient Temp.	-10°C to +30°C
Primary Connections	L & N Screw Down Terminals, Direct to Driver
Secondary Connections	Plug & Play Driver to Head Unit
Accessories	N/A

Performance

Luminous Flux	820 Lumens
Luminous Efficacy (Lm/W)	68 Lm/W
CCT	4000k
CRI (Ra)	Ra:80
Beam Angle	120°
Dimmable	No, Non Dimmable
Tilt/Rotate	No, Fixed Position Luminaire

Construction

Main Chassis	Mild Steel
Trim/Bezel	Aluminium
Diffuser	Polystyrene
Lens	N/A
Heat Sink	Mild Steel
Finish Type	White Powder Coat Paint
Luminaire Weight	TBC

